

Product Data Sheet

## DOW FILMTEC™ NF345HP-370 Element

Description	Ideal for: site managers and operators dealing with challenging separations seeking economical advantages over other membranes, and precipitation processes.				
	<ul> <li>DOW FILMTEC<sup>™</sup> NF345HP-370:</li> <li>Helps reduce the acid mine drainage (AMD) stream, ultimately reducing CAPEX and OPEX</li> <li>Enhances concentration and recovery of valuable metals from AMD waters</li> <li>Provides high permeability, and low pH stability enabling longer</li> </ul>				
Product Type	element lifetime and more reliable operation Spiral-wound element with polyamide thin-film composite membrane				

## **Product Specifications**

	Active Area Feed Space			Permeate	Flow Rate	Typical Stabilized Salt	Minimum Salt
DOW FILMTEC™ Element	(ft²)	(m²)	Thickness (mil)	(GPD)	(m³/d)	Rejection (%)	Rejection (%)
NF345HP-370	370	34	34-LDP	9,000	34	99.2	98.5%

1. Permeate flow and salt passage based on the following test conditions:

2,000 mg/l MgSO<sub>4</sub>, 70 psi (4.8 bar), 77°F (25°C) and 15% recovery.

2. Flow rates for individual elements may vary but will be no more than +/-15%.

 Stabilized salt rejection is generally achieved within 24-48 hours of continuous use; depending upon feedwater characteristics and operating conditions.

4. Sales specifications may vary as design revisions take place.

 Active area guaranteed ± 5%. Active area as stated by Dow Water & Process Solutions is not comparable to nominal membrane area often stated by some manufacturers. Measurement method described in Form No. 609-00434

## B DIA Feed U-Cup Brine Seal

		A	В	C	
DOW FILMTEC™ Element	(in.)	(mm)	(in.) (mm)	(in.)	(mm)
NF345HP-370	40.0	1,016	1.125 ID 29 ID	7.9	201

1. Refer to Dow Water & Process Solutions Design Guidelines for multiple-element applications. 1 inch = 25.4 mm

2. Element to fit nominal 8-inch (203-mm) I.D. pressure vessel.

Page 1 of 2

Element Dimensions

®™ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow

Form No. 609-50181, Rev. 0 August 2015  $(\mathbf{\Phi})$ 

۲

м , , см , , си , си

 $( \bullet )$ 

۲

<b>Operating and</b>	Maximum Operating Temperature <sup>a</sup>	113°F (45°C)				
<b>Cleaning Limits</b>	Maximum Operating Pressure	600 psig (41 bar)				
	Maximum Element Pressure Drop	15 psig (1.0 bar)				
	pH Range, Continuous Operation <sup>a</sup>	2 – 11				
	pH Range, Short-Term Cleaning (30 min.) <sup>b</sup>	1 – 13				
	Maximum Feed Silt Density Index (SDI)	SDI 5				
	Free Chlorine Tolerance °	< 0.1 ppm				
	<ul> <li><sup>a</sup> Maximum temperature for continuous operation above pH 10 is 95°F (35°C).</li> <li><sup>b</sup> Refer to Cleaning Guidelines in specification sheet 609-23010</li> <li><sup>c</sup> Under certain conditions, the presence of free chlorine and other oxidizing agents will cause premature membrane failure. Since oxidation damage is not covered under warranty, Dow Water &amp; Process Solutions recommends removing residual free chlorine by pretreatment prior to membrane exposure. Please refer to technical bulletin <u>"Dechlorinating Feedwater"</u> for more information.</li> </ul>					
Additional Important	Before use or storage, review these additional resources for important information:					
Information	<ul> <li>Usage Guidelines for DOW FILMTEC™ 8" Elements</li> </ul>					
	<u>System Operation: Initial Start-Up</u>					
Regulatory Note	These membranes may be subject to drinking water application restrictions in some countries; please check the application status before use and sale.					
Product Stewardship	Dow has a fundamental concern for all who make, distribute, and use its products, and for the environment in which we live. This concern is the basis for our product stewardship philosophy by which we assess the safety, health, and environmental information on our products and then take appropriate steps to protect employee and public health and our environment. The success of our product stewardship program rests with each and every individual involved with Dow products—from the initial concept and research, to manufacture, use, sale, disposal, and recycle of each product.					
Customer Notice	Dow strongly encourages its customers to their applications of Dow products from the quality to ensure that Dow products are no tested. Dow personnel are available to ans technical support.	review both their manufacturing processes and e standpoint of human health and environmental t used in ways for which they are not intended or wer your questions and to provide reasonable				

DOW FILMTEC<sup>™</sup> Membranes

L

CM MJ

Notice: The use of this product in and of itself does not necessarily guarantee the removal of cysts and pathogens from water. Effective cyst and pathogen reduction is dependent on the complete system design and on the operation and maintenance of the system.

**NOTICE:** No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.



۲

®™ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow

Form No. 609-50181, Rev. 0 September 2015